







Solid framework, large LCD touch screen and advanced QM2.0 software;

High quality optics for crisp and clear images;

Adjustable LED surface and contour illumination;

High resolution industrial CCD camera;

6.5X Detented zoom lens changeable within the range of 30-190x magnification.

Extended function of printing, saving and exporting data;

Excel or Word report output, and DXF input and output;

Non-contact optical height measurement;

Automatic edge-detecting function;

Specifications:

opecinications.		
Model	iVideo-E67	iVideo-E68
X/Z-axis Travel	300×150mm	300×150mm
Y-axis Travel	150mm	200mm
Accuracy	≤4+L/200(um)	
Repeatablitily	±2um	
Operation Mode	Manual	
Sway Range	±15"	
Video Device	1/3" color CCD camera,6.5x Detented zoom lens	
Screen Dimension	19" LCD Touch Screen Monitor	
Video Magnification	30X \sim 190X(it can extend to 15X \sim 380X)	
Working Distance	92mm	
Measuring Software	Quick Measuring 2.0	
Max.Load Capacity	15Kg	
Suitable Environment	Workshop and metrology room	
Dimension(D×W×H)	760×650×1760mm	
Net Weight	200Kg	
1	1	

Standard Delivery:

Measuring Software	Color CCD Camera	Detented Zoom Lens
Calibration Block	Capture Card	LED Illumination
19" LCD Touch Screen	Built-in PC System	Operation Manual